

## NEOFERMA COMPRESSION SEALS

**"One of the worlds best expansion joint systems"**

*Commercial Waterproofing Services are manufacturers and distributors & applicators of Neoferma Compression gaskets.*

- The Neoferma gasket is an extremely flexible hollow rubber section terminating in individual ribs. Neoferma is easily compressed and maintains close contact with concrete, steel or timber surfaces ensuring complete sealing of the joint.
- Unlike traditional sealants Neoferma does not require a primer or bonding agent and can be installed into a wet joint thus reducing the affect of de bonding and joint failure and also reducing construction time.
- Neoferma when used in conjunction with Bentonite, (a swellable clay) offers a double waterproofing barrier. In the event that water passes the Neoferma seal the Bentonite will swell and stop its progress. This double waterproofing system guarantees the joint will stay waterproofed.
- Neoferma is tested to withstand in excess of 10-meter head of water pressure and is UV stable. Neoferma is suitable for use in concrete construction & expansion joints, masonry block wall joints, pools, tanks.
- Neoferma is manufactured from either EPDM or SILICON rubber.
- Silicone rubber can be coloured to match the surface application and has a life expectance of over 50 years.
- Neoferma is ideally suited for swimming pool expansion joints with a potential life expectancy of in excess of 25 years.
- The money saved by keeping the water in can be used to improve facilities in the pool area.

John Muldoon

PH 07 37017240 / Mobile 0402267547 / Email [sales@cwservices.com.au](mailto:sales@cwservices.com.au)